

Compuprint 6210



With Compuprint 6210 on hand, label printing becomes so simple between your fingertips.

Compuprint 6210 is powered by high capacity lithium-ion battery, armored with water/dust/shock resistant feature, supported with drop-and-fit design; it is your ultimate weapon to take on the challenges from mobile applications in retail / warehouse & storage / parking receipt industry and many more.



- Drop & Fit label installation design.
- Long standby time up to 72 hours or 300 label cycles between charges.
- IP54 water / dust resistant and 1.5M shock resistant.
- Supports both wire (RS232 and USB ports)

Model	6210
Print Method	Direct Thermal
Resolution	203 dpi (8 dots/mm)
Print Speed	Up to 4 IPS (101.6 mm/s)
Print Width	2.8" (72 mm)
Print Length	45" (~1142 mm)
Processor	32 Bit RISC CPU
Memory	Flash 128 MB Flash (60 MB for user storage)
	SDRAM 32 MB
Sensor Type	Gap sensor , Fixed transmissive sensor , Fixed reflective sensor
Media	Types Direct Thermal receipt, anti-UV receipt, gap label, center alignment Inter-label gap size from 2 mm to 4 mm. 3 mm preferred
	Width 2.28" (58 mm) fixed
	Thickness Min 0.0508 mm, Max 0.165 mm
	Media roll Diameter Max. 1.57" (40 mm)
Printer Language	POS Emulations or EZPL / EPL Emulations
Software	Label Design Software CPLabel (for EZPL only)
	Driver MAC, Linux, Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1
	DLL Win CE, .NET, Android, Windows Mobile, Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1
Resident Fonts	Bitmap Fonts 6, 8, 10, 12, 14, 18, 24, 30, 16x26 and OCR A & B. 0°, 90°, 180°, 270° rotatable
	TTF Fonts CG Triumvirate™ (Bold / Italic / Underline). 0°, 90°, 180°, 270° rotatable
Download Fonts	Bitmap Fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable
	Asian Fonts 16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese (GB2312), Japanese (S - JIS), Korean (KS - X1001)
	TTF Fonts 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions
Barcodes	1-D Bar codes Code 39, Code 93, EAN 8 / 13 (add on 2 & 5), UPC A / E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC / EAN-128 K - Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar, German Post Code, Planet 11 & 13 digit, Japanese Postnet, I2 of 5 with human readable check digit, Standard 2 of 5, Industrial 2 of 5, Logmars, Code 11, Code 49, Cadablock
	2-D Bar codes PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code and Aztec code.
Code Pages	CODEPAGE 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 WINDOWS 1250, 1251, 1252, 1253, 1254, 1255, 1257
Graphics	Unicode UTF8, UTF16BE, UTF16LE Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the Software
Interfaces	RS232 + USB 2.0 port, mini-B type connector Bluetooth 2.1 + EDR
Control Panel	4 dual color LEDs for Power, Battery, Communication, Error status indication. 3 buttons for Power, Feed and BT functions
Power Adapter	Switching power supply I/P: 100 / 240 V AC, 50 / 60 Hz, DC 9 V / 2.2 A
Battery	Rechargeable DC 7.4 V Lithium-ion battery, 1150 mAH or higher capacitance
Environment	Operation Temperature 32 °F to 122 °F (0°C to 50°C)
	Storage Temperature -4 °F to 140 °F (-20°C to 60°C)
Humidity	Operation 10 – 90 %, non - condensing.
	Storage 10 – 90 %, non - condensing.
IP Rating	Intrusion Protection, IP42 requirement for case design, IP54 for protective case
Drop Level	1.5 meter height
Agency Approvals	CE EMC, FCC part 15B class B, FCC Part 15CCCC, SRRC, NCC, CB, UL, cUL
Dimension	Length 6,65" (169 mm)
	Height 3,03" (77 mm)
	Width 4,41" (112 mm)
Weight	1,65 lbs (750 g), with battery
Options & Accessories	Switching power supply USB cable RS-232 cable Li-ion battery 4-bay battery charger station Car charger adapter Protective case



Compuprint S.r.l.

Via Cottolengo 75-77-79
10072 Caselle T.se (TO)
Sales Contact
Tel. +39 011 9892 141 - Fax +39 011 9974432
sales@compuprint.com
www.compuprint.com