

Compuprint SP 40 Passport

The Compuprint SP 40 is designed to be the ultimate printing solution for transactional applications and financial services. By assuring process efficiency and offering a competitive low cost of ownership, the Compuprint SP 40 is the ideal, long-term asset for businesses and financial institutions.



Very high thickness document printing

- Compact footprint
- Horizontal & vertical passport with automatic variable thickness control
- Easy set-up by configuration sheet
- Fully compatible with today's standard and financial applications
- Powerful system to support future applications and system migration



A leading-edge series for today and tomorrow

The Compuprint SP 40 transactional printer integrates state-of-the-art Compuprint technology and innovation that's based on more than 30 years of leadership in serial dot matrix printer technology. It's built on unsurpassed technologies to offer the most efficient transactional device available in the market. It supports all critical application needs in business and financial industries.

Fast, flexible, reliable

The SP 40 prints documents quickly, clearly and securely. Its ergonomic design and features offer a unique, easy handling of documents at the front desk, allowing users total dedication to their customers.

For a broad range of intensive printing requirements

Equipped with the most flexible and powerful electronics available today, the SP 40 represents the ideal platform for institution and applications developers. It supports all of today's industry-standard applications. It's open platform electronic is ready to support all of the future application or systems migrations.



Printing Technology	24 pin serial dot matrix printer						
Printing speed	<table border="0"> <tr> <td></td> <td>12 cpi</td> <td>10 cpi</td> </tr> <tr> <td>Draft/LQ</td> <td>360 cps/130 cps</td> <td>300/110 cps</td> </tr> </table>		12 cpi	10 cpi	Draft/LQ	360 cps/130 cps	300/110 cps
	12 cpi	10 cpi					
Draft/LQ	360 cps/130 cps	300/110 cps					
Line Length	94 columns @ 10 cpi						
Paper Handling	Single sheet, rigid form, passports, passbook, envelopes, labels Passport from 3,5 mm up to 5.0 mm Single Sheet Width: 65 - 244 mm Single Sheet Length: 70 - 470 mm						
Copies	1 +6						
Special functions	Automatic Gap Adjustment (AGA), Auto Alignment, Auto Border Recognition, Optical Mark Reading, Horizontal and Vertical Passbook Handling, Automatic set-up (automatic recognition of marked values)						
Graphic resolution (dpi)	60,120,180, 240, 360 (horizontal) 72, 90, 180, 216, 360 (vertical)						
Vertical spacing	6-8-12 lines/inch - 3-4-6-8-12 lines/30mm - n/60, n/72, -n/180 - n/216 -n/360 per inch						
Horizontal spacing	5, 6, 7.5, 8.5, 10, 12, 15, 17.1, 20, 24 cpi and proportional						
Barcodes	UPC/A, UPC/E, EAN8, EAN13, Code 39, Code 128, Postnet, Codabar, ADD-ON 2, ADD-ON 5, Code 11, Code 93, BCD, MSI, 2/5 Interleaved, 2/5 Matrix, 2/5 Industrial						
Character set	Code Page:PC standard set (CS1-CS2) - 13 National Epson set - CP437 (USA) - CP437G (Greek) - CP850 (Multilanguage) - CP851 (Greek) - CP852 (Latin 2) - CP853 (Turkish) - CP855 (Russian) - CP857 (Turkish) - CP858 (Euro) - CP860 (Portuguese) - CP862 (Hebrew) - CP863 (French/Canadian) - CP864 (Arabic) - CP865 (Norwegian) - CP866 (Cyrillic) - CP867 (Turkish) - CP876 (OCRA) - CP877 (OCRB) - CP1250 (Central Europe) - CP1251 (Cyrillic) - CP 1252 (Windows Latin1 Ansi) - Gost - Tass - Mazowia - ISO 8859/1/2/3/4/5/6/7/8/9/15 - 96GREEK - Ukrainian - ID 12 - ID 14 - ID 17 - CP1098 (Farsi Arabic) - Roman 8 - CP 437 Slavic - Sanyo- Ku - PhilipOlivetti Character CS000 - CS010 International, CS020 Germany, CS030 Portugal, CS040 Spain1,SetCS050 Denmark/Norway, CS060 France, CS070 Italy, CS080 Sweden/Finland, CS090 Switzerland, CS100 Great Britain, CS110 USA ASCII, CS140 Greece, CS150 Israel, CS170 Spain 2, CS200 Jugoslavia, CS410 Olivetti TCV 370, CS510 SDC, CS520 Turkey, CS540 CIBC, CS680 OLI-UNIX, CS701 PC-220 Spain2, CS711 PC-Denmark/Norway, CS712 PC-Denmark OPE, CS771 PC-210 Greek						
Resident font	Draft, Courier, Gothic, Prestige, Presentor, Script, OCR-A, OCR-B, Boldface						
Resident Emulations	IBM ® Personal Printer 2390+, Proprinter XL24E, Proprinter XL24E-AGM and Epson ® LQ2550/LQ1170, IBM ® 4722, Olivetti ® PR40 plus/PR2/PR2845, IBM 9068						
Interfaces	Parallel IEEE 1284 bidirectional, Serial RS-232 C (Automatic Interface Switching) Input buffer up to 64 Kbytes Plug&play (Windows environments)						
Reliability	MTBF: 10.000 hours						
Print Head Life	400 million characters						
Ribbon life	Black ribbon cartridge: 5 million characters or Long life 15 million characters						
Noise Level	< 55dba						
Power Supply	Universal from 100 to 230 V Frequency: 60Hz / 50Hz						
Power consumption	75 W max. (printing), 7 W (standby)						
Physical Dimensions & Weight	400 (W) x 200 (H) x 295 (D) mm - <12 Kg						



COMPUPRINT SALES CONTACTS

Italy: (+39) 011 9892 141
Other Countries: (+39) 011 9892 141
Email: sales@compuprint.com
Website: www.compuprint.com

Ordering Information

Printers and Supplies

Compuprint SP 40 passport	PRT0550
6 black ribbons 5 MC	PRK5286-6
6 black ribbons 15 MC	PRK5290-6



The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.
Copyright © 2010 Compuprint