



Impact solutions for business and logistic environments

Compuprint 2056e

Compuprint 2056e satisfies typical needs in hospitals, hotels, retail stores, as well as in industrial and logistics environments.

As a very economical printer the Compuprint 2056e helps to save money with its longlife ribbon of 10 million characters and its low power consumption.

Compuprint 2056e is the best choice for printing applications using multipart forms, single sheets, labels and envelopes.



Values and Features

- ✓ 24 pins print head (up to 500 Mio. strokes/pin)
- ✓ Interfaces: parallel, USB 2.0, RS-232C, I/O V
- ✓ great impact: 1 + 5 copies
- ✓ up to 400 characters/second
- ✓ Workload: up to 10.000 pages a month
- ✓ Automatic pin alternation

Versatile, economic and reliable

The Compuprint 2056e is most economic both in terms of its price and on duty. With an easy to use operator panel, low printing noise and multiple interfaces included as standard the Compuprint 2056e is user friendly.

The Compuprint 2056e brings higher levels of print quality to general business and point of sale applications producing invoices, receipts, dispatch notes, labels and end of day reports.



Compuprint 2056e – Your most economic network printer

Printer Model	2056e
Print Technology	Serial Dot Matrix Printer
Printhead	24 pins (Ø 0,22 mm), Lifetime: 500 Mio strokes/pin
Print Speed	10 cpi: Very High Speed Draft 400 cps, High Speed Draft 300 cps, Draft 150 cps, LQ 100 cps
Print Width	Max. 80 columns @ 10 characters/inch
Paper Handling	+ Continuous Form: rear loading – paper width: 56 – 267 mm + Cut Sheet: paper width: 48 – 261 mm, weight: 52 – 90 g/m2 + Label: width of liner 101,6 – 254 mm, smallest label: 63.5 mm x 23.8 mm weight: max. 68 g/m2
Copies	1+ 5 - max. thickness: 0.52 mm
Special Functions	+ Automatic pin alternation (for decrease the workload on pins used most frequently) + smart pin surveillance to substitute broken pins + Printer configuration by remote control (PC-Software)
Graphic Resolution	360 dpi x 360 dpi
Vertical Spacing	6 lines per inch; 8 lines per inch; n/360 per inch
Horizontal Spacing	10, 12, 15, 17, 20 cpi and proportional
1D-Codes (Barcodes)	EAN 8, EAN 13, 2/5 Interleaved, 2/5 Matrix, 2/5 Industrial, Code 39, Code 128, NW-7
Fonts	Draft, Courier, OCR-A, OCR-B, Prestige, Presentor, Roman, Sans Serif, Script
Character Sets	17 international character sets: U.S.A, France, Germany, U.K, Denmark 1 & 2, Sweden, Italy, Spain 1 & 2, Japan, Norway, Latin Am, Korea, Legal, Netherlands, Turkey IBM and EPSON character sets: CP 437 (USA), CP437G (Greek), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP 861 (Island), CP863 (French-Canadian), CP860 (Portugal), CP865 (Danish-Norwegian), CP866 (Russian), CP1250 (Latin2 Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), MAZOWIA, KAMENICKY, ISO Latin 1, 2, 7, 9, BULGARIA, HUNGARY, ARAB NLS, ARAB EXT, KBL
Emulation	Epson ® LQ ESC/P2, IBM ® Personal Printer 2391
Driver	Windows 2000/XP/7/8 Server 2003/2008
Interfaces	Parallel IEEE1284 bidirectional, USB 2.0 (Full Speed) or Parallel, USB 2.0, Serial, LAN
Buffer	256 KB
Ribbon life	Black ribbon, > 10 Mio. Characters in draft
Noise	< 53 dB (A) (ISO 7779 Standard)
Power Supply	Std: 176 – 242 V - (100V – 110 V on request) Frequency: 50 Hz - (60 Hz 110 V)
Power Consumption	Printing: 70 W on average, Standby: 4,6 W
Dimensions	Depth: 28,0 cm, Width: 38,4 cm, Height: 13,9 cm
Weight	6 kg
Duty Cycle	20%

Printer and Supplies

Compuprint 2056e with par, USB 2.0	PRT2056E
Compuprint 2056e with par, ser, USB 2.0, LAN	PRT2056EN
Black ribbon, 10 Mio. char in draft	PRK2080-1

Compuprint

Via Cottolengo 77
10072 Caselle T.se (To)
ITALY
Phone: +39 011-9892-133
sales@compuprint.com
www.compuprint.com

