



The **fastest** Serial Printer today available in the Printing World

Compuprint 9300 adopts enhanced and improved electronic and mechanical solutions that move the real print performance to an unbeatable level

860 Page per Hour
600 Lines per Minute
800 Million Characters Print Head Life

Compuprint
9300e

The combination of such print performance with eight copies capability, dual tractors, wide range of barcodes, macrocharacters, ease of use, emulations, interfaces and the extraordinary global reliability make the **Compuprint 9300e simply unique**

Value and Features

- 18 pins print-head with 800 Million Characters life
- 860 Pages Per Hour (PPH)
- 600 Lines Per Minute (LPM)
- Superior performance in volume printing
- Dual front straight paper paths
- 1 + 9 copies capability
- Simple to use, pre-set configurations
- Wide range of barcodes and macro-characters
- Parallel, Serial, USB and LAN interfaces



A leading-edge printer for today and tomorrow

Compuprint 9300e integrates the latest technology and innovation based on more than 30 years of Compuprint leadership in the serial printer technology. It represents the preferred choice for business and industrial printing applications requiring up to 75.000 pages per month workload.

Fast, flexible, reliable

The Compuprint 9300e is designed with state-of-the art technologies and innovative functionalities. It provides two front continuous paper paths with 6 pins tractors equipped with paper run sensors, automatic paper path alternance, paper thickness recognition, paper parking/loading and zero tear off. All with the superb reliability of 20.000 hours of MTBF.

For a broad range of connectivity and printing requirements

The Compuprint 9300e is available with different interface configurations, Parallel/USB/Serial or Parallel/LAN. Optionally is available the IPDS over LAN interface for OS/400 environments. A large number of character sets, fonts and barcodes combined with a wide set of protocols allow to use the printer in most contemporary environments and to be the ideal solution for industrial requirements for printing macro characters, barcodes on statements, labels and pre-printed forms.

Printing Technology	18 pin serial dot matrix printer - 136 columns @ 10 cpi		
Real Throughput (note 1)			ISO/IEC 10561
	Char. per line	40 80 100	DIN Letter 10cpi
	LPM	600 440 390	PPH 860 Spreadsheet 10cpi 560
Printing speed (@10 cpi) (correlated to throughput data - compared with competition)	CPS	HSD 10cpi	Draft 10cpi NLQ 10cpi
		1600	1360 340
Paper handling	Continuous form: front loading Front push tractor 6 pin (BASE CONFIGURATION) Additional front push tractor 6 pin (opt.)		
Copies	1 + 9		
Special functions	Automatic paper path alternance Automatic Gap Adjustment (AGA) of print head based on paper thickness Zero tear-off Automatic paper parking of continuous form		
Graphic resolution (dpi)	Printing Resolution 240 x 144 (max.)		
Vertical spacing	6 - 8 - 12 lines per inch; 3 - 4 - 6 - 8 - 12 lines per 30 mm.; n/60, n/72, n/216 per inch		
Horizontal spacing	10, 12, 15, 17.1, 20 cpi and proportional		
Barcodes	UPC/A, UPC/E, EAN8, EAN13 - UPC/EAN ADD-ON 5, UPC/EAN ADD-ON 2 - Code 39 - Code 128 - Code 11- Code 93 - MSI - Postnet - Codabar - 2/5 Interleaved - 2/5 Matrix - 2/5 Industrial - Code GP - C25-3BAR - Code BCD - 2/5 Bidirectional		
Character set	Standard PC IBM character sets: CS1, CS2 ; 13 EPSON national variations IBM and EPSON character sets: CP 437 (USA), CP437G (Greek), CP437SL (Slavic), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP857 (Turkish), CP858 (Euro PC Multilingual), CP860 (Portugal), CP862 (Hebrew), CP863 (French-Canadian), CP864 (Arabic), CP865 (Danish-Norwegian), CP866 (Russian), CP867 (Turkish2), CP876 (OCR-A), CP877 (OCR-B), CP1098 (Farsi), CP1250 (Latin2 Windows), CP1251 (Cyrillic Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), CP1254 (Turkish Windows), CP1255 (Hebrew Windows), CP1256 (Arabic Windows), CP1257 (Baltic Windows), 96Greek, GOST, TASS, MAZOWIA, KOI8-U ISO character sets: 8859/1 (Latin1), 8859/2 (Latin2), 8859/3 (Latin3), 8859/4 (Latin4), 8859/5 (Latin/Cyrillic), 8859/6 (Latin/Arabic), 8859/7 (Latin/Greek), 8859/8 (Latin/Hebrew), 8859/9 (Latin5), 8859/15 (Latin9) Draft, Courier, Gothic, DP Text, OCR-A, OCR-B		
Resident font	Epson ® FX Series, IBM ® Proprinter III XL, IBM ® Personal Printer 2381, ANSI, Compuprint native commands		
Resident Emulations	Parallel - Ethernet 10/100 or Parallel - Serial - USB or Parallel - LAN/IPDS		
Interfaces	Input buffer 128 Kbytes - Plug&play (Windows environment)		
Drivers and Sw	Windows 9X/2000/XP/Vista - NOVEL - DOS NetViewMaster (complete printer management from remote) and Internal WEB Page (both available with LAN interface)		
Reliability	MTBF: 20.000 hours		
Print Head Life	800 Millions Characters		
Ribbon life	Black Long life ribbon 25 Millions Characters		
Noise Level	54 dBA		
Power Supply	Tension: 100V - 240V Frequency: 60 Hz - 50 Hz		
Power consumption	120 W Max. (printing), 30 W (standby)		
Physical Dimensions & Weight	670 (W) x 320 (H) x 450 (D) mm - 21 Kg		



Compuprint SALES CONTACTS

Italy: (+39) 011 9892 141 -
Other Countries: (+39) 011 9892 141 -
Website: www.compuprint.com
Email: sales@compuprint.com



Ordering Information

Printers and Supplies

Compuprint 9300e - Par/Ser/USB	PRTN9300
Compuprint 9300e - Par/Lan	PRTN9300N
Compuprint 9300e - Par/Lan-IPDS	PRTN9300I
Black ribbon 25MC	PRKN102-1

Options

Additional tractor	PRFN2TR6
Open pedestal	PRFN-PD1
Controller Interface Par/Ser/USB	PRAN930
Controller Interface Par/Lan	PRAN930N
Controller Interface Par/Lan-IPDS	PRAN930I

Note 1 - The Compuprint 9300e measured performance herein declared are superior than any other competitive serial matrix printer model

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.
Copyright © 2008 Compuprint