

# Compuprint

● ● ● ● *Printing and Scanning Solutions*

A truly “state of the art”

## **Transactional Multifunction Printer**

for Front Office and Financial Applications



*COMPACT  
MODERN DESIGN  
FAST AND RELIABLE  
LOW COST OF OWNERSHIP  
LOW POWER CONSUMPTION*

## **Compuprint SP40 *plus***



# Environmentally Friendly

# Compuprint

● ● ● ● Printing and Scanning Solutions

## Compuprint SP40 plus - Transactional Multifunction Printer

### Technical Data

Printing Technology	Impact Dot Matrix 24 pin
Print Speed (@ 10 cpi)	660 cps (VHSD), 520 cps (HSD), 400 cps (Draft), 200 cps (NLQ), 133 cps (LQ), BIM: 2400 dps
Line Length	94 columns @10 cpi, 112 columns @12 cpi, 141 columns @15 cpi
Horizontal Spacing	5, 6, 7.5, 8.5, 10, 12, 15, 16.6, 17.1, 20, 24 cpi and proportional
Paper Handling	Single sheet, envelopes, label: thickness 0,065 ÷ 0,65 mm, weight 40 gr/m <sup>2</sup> ÷ 200 gr/m <sup>2</sup> Passbook (horizontal and vertical): thickness up to 2,8 mm Size (wxh): 65 x 65 mm (min) 244 x 500 mm (max)
Copies	1 original + 6 copies
Special Functions	Automatic Gap Adjustment (AGA), Document Auto Alignment, Bidirectional Logic Seeking Auto Border Recognition, Optical Mark Reading, Automatic Set-up
Display	LCD display – 2 lines with 16 characters each
Graphic Resolution	60, 120, 180, 240, 360 horizontal – 72, 90, 180, 216, 360 vertical
Character Set	21 International Code Page, 28 International Character Set, Gost, Mazovia, Farsi
Barcodes	UPC A/E, EAN 8/13, Code 11/39/93/128, ADD-ON 2/5, BCD, MSI, 2/5 Interleaved, 2/5 Matrix, 2/5 Industrial, Postnet, Codabar
Resident Font	Draft, Courier, Gothic (Sans Serif), Roman, Prestige, Presentor, Script, OCR-A/B, Boldface, Italic
Resident Emulations	IBM Personal Printer 2390+, IBM Proprinter XL24-XL24AGM, Epson LQ2550/LQ1170/ESC/P IBM 4722, Olivetti PR40plus/PR2/PR2845, IBM 9068, HPR 4915, UNISYS EFP Series
Interface	Standard: Parallel, Serial RS-232 C, USB 2.0 Full Speed (Automatic Interface Switching) Optional: 2nd Serial, 2nd USB device High Speed, Ethernet 10/100, up to 3 USB Hub ports, USB Host (2.0 Full Speed OHC) Input buffer up to 128 Kbytes
Drivers	Windows 2000, XP, Vista (32-64 bits), Windows 7 (32-64 bits)
Reliability	MTBF > 10.000 hours – MTRR 16 minutes
Print Head	24 needles, life > 400 million characters (equivalent to > 1 Billion strokes/wire)
Consumables	Black ribbon, life > 10 million characters
Noise Level	< 52 dB (A)
Power Supply	Universal 100-230 V, 60-50 Hz Power consumption: 45 W (ISO/IEC 10561 Letter pattern) – Sleep Mode < 3W – Off Mode 0W Energy Star compliant
Dimensions and weight	396 (W) x 200 (H) x 285 (D) mm – 8 Kg (9,2 Kg packed)



### Optional Devices

Scanner	Front/rear colour scanner, 16 million colours RGB, 256 grey levels, up to 600 dpi, Twain compatible, scan size from ID card to A4. Scanning speed (front/rear): up to 15 inch/sec Mono. up to 7.5 inch/sec Colour
MSRW	Magnetic strip read/write, 4 bit code – Reading speed 13 inch/sec Characters: ASCII 30-3F, Field dupl., DIN 32774, ANSI, IBM 3604, Burroughs
MICR	MICR reader – Reading speed 27 inch/sec CMC7 and E13B supported

**Specific version with rear tractor for fanfold** (max. width 9,45 inch)

### Product Models

Compuprint SP40 plus w/o Display	PRT0620
Compuprint SP40 plus Display	PRT0626e
Compuprint SP40 plus Display LAN	PRT0626-LAN
Compuprint SP40 plus Display Dual USB	PRT0627
Compuprint SP40 plus Display Dual serial	PRT0628
Compuprint SP40 plus Display MSRW-MICR	PRT0630
Compuprint SP40 plus Display Scanner	PRT0631
Compuprint SP40 plus Display Scanner-MSRW-MICR	PRT0632
Compuprint SP40 plus Display LAN with Rear tractor	PRT0626-T

### Consumables

#6 Black ribbons – 10MC	PRK6287-6
#6 Black ribbons – 16MC	PRK6290-6



### Compuprint S.r.l.

Via Lombardore, 282  
10040 Leini (TO) - Italy  
Sales Contact  
Tel. +39 011 9892 141 - Fax +39 011 9974432  
sales@compuprint.com  
[www.compuprint.com](http://www.compuprint.com)

Copyright © 2013 Compuprint Srl

The information contained in this document are subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.