



Impact solutions for business and logistic environments

Compuprint 2056e

Compuprint 2056e satisfies typical needs in hospitals, hotels, retail stores, as well as in industrial and logistics environments.

As a very economical printer the Compuprint 2056e helps to save money with its longlife ribbon of 10 million characters and its low power consumption. Compuprint 2056e is the best choice for printing applications using multipart forms, single sheets, labels and envelopes.



Values and Features

- ✓ 24 pins print head (up to 500 Mio. strokes/pin)
- ✓ up to 4 interfaces: parallel, USB 2.0, serial and LAN
- ✓ great impact: 1 + 5 copies
- ✓ up to 420 characters/second
- ✓ Workload: more than 10.000 pages a month
- ✓ Automatic pin alternation
- ✓ Universal power supply

Versatile, economic and reliable

The Compuprint 2056e is the most economic both in terms of its price and on duty. With an easy-to-use operator panel, low printing noise and multiple interfaces included as standard, the Compuprint 2056e is user friendly.

The Compuprint 2056e brings higher levels of print quality to general business and point of sale applications producing invoices, receipts, dispatch notes, labels and end of day reports.

Printer Model	2056e
Print Technology	Serial Dot Matrix Printer
Print head	24 pins (Ø 0,22 mm), Lifetime: > 500 Million strokes/pin (equivalent to 200 million characters)
Print Speed(*)	10 cpi: Very High Speed Draft 420 cps, High Speed Draft: 340 cps, Draft 170 cps, LQ 112 cps
Print Width	Max. 80 columns @ 10 characters/inch
Paper Handling	+ Continuous Form: rear loading – paper width: 56 – 267 mm + Cut Sheet: paper width: 48 – 261 mm, weight: 52 – 90 g/m2 + Label: width of liner 101,6 – 254 mm, smallest label: 63.5 mm x 23.8 mm weight: max. 68 g/m2
Copies	1+ 5 - max. thickness: 0.52 mm
Special Functions	+ Automatic pin alternation (for decrease the workload on pins used most frequently) + Smart pin surveillance to substitute broken pins + Printer configuration by remote control (PC-Software)
Graphic Resolution	360 dpi x 360 dpi
Vertical Spacing	6 lines per inch; 8 lines per inch; n/360 per inch
Horizontal Spacing	10, 12, 15, 17, 20 cpi and proportional
1D-Codes (Bar codes)	EAN 8, EAN 13, 2/5 Interleaved, 2/5 Matrix, 2/5 Industrial, Code 39, Code 128, NW-7
Fonts	Draft, Courier, OCR-A, OCR-B, Prestige, Presenter, Roman, Sans Serif, Script
Character Sets	17 international character sets: U.S.A, France, Germany, U.K, Denmark 1 & 2, Sweden, Italy, Spain 1 & 2, Japan, Norway, Latin Am, Korea, Legal, Netherlands, Turkey IBM and EPSON character sets: CP437 (USA), CP437G (Greek), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP861 (Island), CP863 (French-Canadian), CP860 (Portugal), CP865 (Danish-Norwegian), CP866 (Russian), CP1250 (Latin2 Windows), CP1251 (Cyrillic), CP1252 (Latin1 Windows), CP1253 (GreekWindows), MAZOWIA, KAMENICKY, ISO Latin 1, 2, 7, 9, BULGARIA, HUNGARY, ARAB NLS, ARAB EXT, KBL
Emulation	Epson ® LQ ESC/P2, IBM ® Personal Printer 2391
Driver	Windows 2000/XP/7/8/10/11 (32 & 64 bit), Server 2003/2008, Linux
Interfaces	Parallel IEEE1284 bidirectional, USB 2.0 (Full Speed) or Parallel, USB 2.0, Serial, LAN
Buffer	256 KB
Reliability	MTBF > 10.000 hours (IEC 605.7 standard)
Ribbon life	Black ribbon, > 10 Million Characters in draft
Noise	<53 dB (A) (ISO 7779 Standard)
Power Supply	Voltage: AC 110V~240V Frequency: 50/60Hz
Power Consumption	Printing: 70 W on average, Standby: 4,6 W
Dimensions	Depth: 28,0 cm, Width: 38,4 cm, Height: 13,9 cm
Weight	6 kg
Options	Roll Paper Holder (On Request)

(*) correlated to throughput data - compared with competition



Printer and Supplies

Compuprint 2056e with par, USB 2.0	PRT2056E (On request)
Compuprint 2056e with par, ser, USB 2.0, LAN	PRT2056EN
Black ribbon, 10 Million characters in draft	PRK2080-1

GDS S.p.a. – Compuprint Division

Via Cottolengo 79
10079 Mappano (To)
ITALY
Phone: +39 011 9892 -141-133
sales@compuprint.com
www.compuprint.com

