




Compuprint 6114 Pro



The economical high-performance 4-inch desktop label printer

The **Compuprint 6114 Pro** sets a new standard for **affordable, high-quality thermal printing**. Designed for **easy-to-use and reliability**, this compact printer fits seamlessly into any workspace while delivering excellent performance and long-lasting durability.

MAIN FEATURES



Versatile Connectivity
Comes with USB, Ethernet, and
Serial interfaces as standard



Dual Printing Technology
Supports both thermal transfer
and direct thermal printing

APPLICATIONS



Manufacturing & Warehousing

Retail & Logistics

Healthcare & Laboratories

Labeling of products

Hospitality & Entertainment

TECHNICAL DATA

PRT6114PRO

PRT6114-HPRO

Print Method	Thermal Transfer / Direct Thermal	
Resolutions	203 dpi (8 dot/mm)	300 dpi (12 dot/mm)
Print Speed	Up to 5 IPS (127 mm/s)	Up to 4 IPS (102 mm/s)
Print Width	4,25" (108 mm)	4,16" (105,7 mm)
Print Length	Min 0,16" (4 mm)- Max 68"(1727 mm)	Min. 0,16" (4 mm)- Max 30"(762 mm)
Memory	Flash 8 MB (4MB for user storage)	SDRAM 16MB
Sensor Type	Adjustable reflective sensor (full range) . Fixed transmissive sensor	
Media	Width 1"(25,4mm) Min - 4,65 "(118mm) Max Thickness 0,003"(0,076mm)Min—0,008"(0,20mm) Max Label roll diameter 5" (127 mm) Core diameter 1" (25,4 mm) 1,5" (38,1 mm)	
Ribbon	Types: Wax, Wax/ resin, Resin Length 360 (110 m) Width Min 1,18" (30 mm)— Max 4,33" (110mm) Ribbon roll diameter 1,57" (40 mm) Core diameter 0.5" (12,7 mm)	
Printer Language	CEL , CZL automatic switching— CEL (Language Compuprint Eltron) CZL (Language Compuprint Zebra)	
Software	Label Design Software: CPLabel Driver : Vista, Win 7/8/8.1/10/11/ Server ,2008,2008R2,2012,2012R2,2016,2019 MAC , Linux SDK Windows CE, .NET , Win7, Win 8 & 8.1, Win10, Win 11,Android,Mac,iOS	
Resident Fonts	Bitmap Fonts 6,8,10,12,14,18,24,30,16x26 and OCR A&B - Bitmap Fonts 0° 90°,180°,270° rotatable , single character 0° 90°,180°,270° rotatable — 8 times expandable horizontal and vertical directions TTF Fonts (Bold/Italic/Underline) 0° 90°,180°,270° rotatable	
Download Fonts	Bitmap Fonts 0°90°,180°,270° rotatable Asian Fonts 6 x 16,24x24.Chinese traditional TTF Fonts (Bold/Italic/Underline) 0°90°,180°,270° rotatable	
Barcodes	1-D Bar Codes Code 39,93, EAN 8/13 (add on 2&5), UPC A/E (add on 2&5), I 2 of 5 & I2 of 5 with Shipping Bearer Bars, Codabar,, Code 128 (subset A,B, C) EAN 128, RPSA128,,UCC 128, ,UCC/EAN 128 K-Mart, Random weight , Post NET, ITF14, China Postal code, HIBC,MSI,Plessey, Telepen,FIM,GS1 Databar 2-D Bar Codes PDF417,,Datamatrix code,Maxicode, QRCode,,MicroPDF417,Micro QRCode , Aztec code	
Code Pages	CODEPAGE 437,850,851,852,855,857,860,861,862,863,865,866,869,737 WINDOWS 1250,1251,1252,1253,1254,1255,1257 Unicode (<utf8, UTF16)	
Graphics	Resident graphic file types are : BMP and PCX, other graphic formats are downloadable from the software	
Interfaces	USB 2.0—Serial Port RS-232 (DB-9) - Ethernet 10/100 Mbps	
Control panel	One tricolor Led (Green,Orange and Red) Function Key: FEED Calibration Button	
Real Time Clock	Available as optional (dealer install)	
Power	Switching Power, 100-240 VAC , 50-60 Hz	
Environement	Operation Temperature 41°F to 104°F (5°C to 40° C) - Storage temperature -4° to 122° (-20° to 50° C)	
Umidity	Umidity operation 30-85%, Umidity storage 10—90 % ,	
Agency Approval	CE (EMC)	
Dimension	Length 251mm Height 164mm Width 200mm	
Weight	1,8 Kg consumables exluded	
Options	Cutter (dealer Install / External Label unwind stand / External label rewinder / Bluetooth / LAN wireless	

GDS S.p.a. - Compuprint Division

Via Cottolengo 79
10079 Mappano (TO)
Sales Contact
Tel. +39 011 9892141 - Fax +39 011 9974432
sales@compuprint.com
www.compuprint.com

