




Compuprint 6214 Pro




High-Performance 4-Inch Desktop Label Printer

The **Compuprint 6214 Pro** is a powerful and versatile **thermal label printer**, designed for businesses that require **fast, high-quality printing** across various industries. Whether for **logistics, healthcare, manufacturing, retail, or ticketing**, this printer delivers outstanding efficiency and reliability.

MAIN FEATURES




Multilingual LCD Display
User-friendly color screen for easy operation



Wireless Connectivity
Supports wireless connectivity via Bluetooth or USB WiFi dongles for seamless integration

802.1X

Secure Network Access
Advanced authentication features for safe and encrypted connections




Versatile Connectivity
The two USB Host ports enable the connection of USB peripherals, enhancing efficiency and usability



Direct PDF Printing
Print PDFs directly from Windows, Linux, Android, iOS, and Mac without conversion.

APPLICATIONS



Retail & Manufacturing



Logistics & Warehousing



Healthcare & Pharmaceuticals



Jewelry & Fashion

TECHNICAL DATA

PRT6214PRO

PRT6214-HPRO

Print Method	Thermal Transfer / Direct Thermal	
Resolutions	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
Print Speed	Up to 7 IPS (177 mm/s)	Up to 5 IPS (127 mm/s)
Print Width	4,25" (108 mm)	4,16" (105,7 mm)
Print Length	Min. 0,12" (3 mm)- Max 400"(10,160 mm)	Min. 0,12" (3 mm)- Max 350"(8,890 mm)
Memory	Flash 16 GB SDRAM 512MB	
Sensor Type	Adjustable reflective sensor (full range)—Fixed trasmissive sensor, central aligned	
Media	Width 0,79"(20mm) Min - 4,65 "(118mm) Max Thickness 0,0024"(0,06mm)Min—0,081"(0,2mm) Max Label Roll Diameter Max 5" (127 mm) Core Diameter 1" (25,4 mm) 1,5" (38,1 mm)	
Ribbon	Types Wax,, wax/resin, resin Length 981 (300 m) Width 1,18" (30 mm) Min—4,33" (110mm) Max Ribbon Roll Diameter 2,67" (68 mm) Core Diameter 1" (25,4 mm)	
Printer Language	CEL , CZL auto switch— CEL (Compuprint Eltron Language) CZL (Compuprint Zebra Language)	
Software	PDF Docs : Supports to print PDF documents - Label Design Software : CPLabel— GoApp (Android/iOS) Driver : Win XP SP2 ,or later , Vista, Win 7/8/8.1/10/11/ Server 2003 ,2008,2008R2,2012,2012R2 32/64 bit SDK Windows CE, .NET , Win7, Win 8 & 8.1, Win10, Win 11,Android,Mac,iOS	
Resident Fonts	Bitmap Fonts 6,8,10,12,14,18,24,30,16x26 and OCR A&B - 90°,180°,270° rotatable , single carachters 90°,180°,270° rotatable — 8 times expandable in horizontal and vertical directions Scalable Fonts 90°,180 °,270° rotatable	
Download Fonts	Bitmap Fonts 90°,180°,270° rotatable Asian Fonts 90°,180°,270° rotatable and 8 times expandable in horizontal and vertical directions Scalable Fonts Scalable fonts 90°,180°,270° rotatable	
Barcodes	1-D Bar Codes Code 39,93, EAN 8/13 (add on 2&5), UPC A/E (add on 2&5), I 2 of 5 & I2 of 5 with Shipping Bearer Bars, Codabar,, Code 128 (subset A,B, C) EAN 128, RPSA128,,UCC 128, ,UCC/EAN 128 K-Mart, Random weight , Post NET, ITF14, China Postal code, HIBC,MSI,Plessey, Telepen,FIM,GS1 Databar 2-D Bar Codes PDF417,,Datamatrix code,Maxicode, QRCode,,MicroPDF417, Micro QRCode , Aztec code	
Code Pages	CODEPAGE 437,850,851,852,855,857,860,861,862,863,865,866,869,737 WINDOWS 1250,1251,1252,1253,1254,1255,1257 Unicode (<utf8, UTF16)	
Graphics	Resident graphics file types are BMP and PCX, other graphic formats are downloadable from the SW	
Interfaces	USB 2.0—Serial Port RS-232 (DB-9) - Ethernet 10/100 Mbps - USB Host x 2	
Control Panel	Color TFT LCD with navigation button—Calibration button — Power On/Off button	
Real Time Clock	Standard	
Power	Auto Switching 100-240 VAC , 50-60 Hz	
Environements	Operation Temperature 41°F to 104°F (5°C to 40° C) - Storage Temperature -4° to 122° (-20° to 50° C)	
Umidity	Operation 30-85%, non condensing Storage 10—90 % , non condensing	
Agency Approval	CE (EMC)	
Dimension	Length 280mm Height 186mm Width 210mm	
Weight	3 Kg excluding consumables	
Options	Cutter Module / Label Dispenser / Exthernal Label unwind stand / External Label Rewinder	

GDS S.p.a. - Compuprint Division

Via Cottolengo 79
10079 Mappano (TO)
Sales Contact
Tel. +39 011 9892141 - Fax +39 011 9974432
sales@compuprint.com
www.compuprint.com

