Impact solutions for industrial and business environments

The **fastest** Serial Printer today available in the Printing World

Compuprint 9300 adopts enhanced and improved electronic and mechanical solutions that move the real print performance to an unbeatable level

860 Page per Hour
600 Lines per Minute
800 Million Characters Print Head Life

Compuprint 9300e

The combination of such print performance with eight copies capability, dual tractors, wide range of barcodes, macrocharacters, ease of use, emulations, interfaces and the extraordinary global reliability make the **Compuprint 9300e simply unique**

Value and Features

- **18** pins print-head **with 800 Million Characters life**
- **860 Pages Per Hour (PPH)**
- **600 Lines Per Minute (LPM)**
- Superior performance in volume printing
- Dual front straight paper paths
- **1 + 9** copies capability
- Simple to use, pre-set configurations
- Wide range of barcodes and macro-characters
- **Parallel, Serial, USB and LAN interfaces**

A leading-edge printer for today and tomorrow

Compuprint 9300e integrates the latest technology and innovation based on more than 30 years of Compuprint leadership in the serial printer technology.
It represents the preferred choice for business and industrial printing applications requiring up to 75.000 pages per month workload.

Fast, flexible, reliable

The Compuprint 9300e is designed with state-of-the art technologies and innovative functionalities.
It provides two front continuous paper paths with 6 pins tractors equipped with paper run sensors, automatic paper path alternance, paper thickness recognition, paper parking/loading and zero tear off.
All with the superb reliability of 20.000 hours of MTBF.

For a broad range of connectivity and printing requirements

The Compuprint 9300e is available with different interface configurations, Parallel/USB/Serial or Parallel/LAN. Optionally is availble the IPDS over LAN interface for OS/400 environments.
A large number of character sets, fonts and barcodes combined with a wide set of protocols allow to use the printer in most contemporary environments and to be the ideal solution for industrial requirements for printing macro characters, barcodes on statements, labels and pre-printed forms.

GDS Compuprint

Technical Specifications

Compuprint 9300e

Printing Technology	18 pin serial dot matrix printer - 136 columns @ 10 cpi
Real Throughput (note 1)	ISO/IEC 10561 Char. per line 40 80 100 — DIN Letter 10cpi — Spreadsheet 10cpi LPM 600 44 0 390 — PPH 860 — 560
Printing speed (@10 cpi) (correlated to throughput data - compared with competition)	CPS — HSD 10cpi: 1600 — Draft 10cpi: 1360 — NLQ 10cpi: 340
Paper handling	Continuous form: front loading Front push tractor 6 pin (BASE CONFIGURATION) Additional front push tractor 6 pin (opt.)
Copies	1 + 9
Special functions	Automatic paper path alternance Automatic Gap Adjustment (AGA) of print head based on paper thickness Zero tear-off Automatic paper parking of continuous form
Graphic resolution (dpi) ·	Printing Resolution 240 x 144 (max.)
Vertical spacing·	6 - 8 - 12 lines per inch; 3 - 4 - 6 - 8 - 12 lines per 30 mm.; n/60, n/72, n/216 per inch
Horizontal spacing·	10, 12, 15, 17.1, 20 cpi and proportional
Barcodes·	UPC/A, UPC/E, EAN8, EAN13 - UPC/EAN ADD-ON 5, UPC/EAN ADD-ON 2 - Code 39 - Code 128 - Code 11- Code 93 - MSI - Postnet - Codabar - 2/5 Interleaved -2/5 Matrix - 2/5 Industrial - Code GP - C25-3BAR - Code BCD - 2/5 Bidirectional
Character set	**Standard PC IBM character sets:** CS1, CS2 ; 13 EPSON national variations **IBM and EPSON character sets:** CP 437 (USA), CP437G (Greek), CP437SL (Slavic), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP857 (Turkish), CP858 (Euro PC Multilingual), CP860 (Portugal), CP862 (Hebrew), CP863 (French-Canadian), CP864 (Arabic), CP865 (Danish-Norwegian), CP866 (Russian), CP867 (Turkish2), CP876 (OCR-A), CP877 (OCR-B), CP1098 (Farsi), CP1250 (Latin2 Windows), CP1251 (Cyrillic Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), CP1254 (Turkish Windows), CP1255 (Hebrew Windows), CP1256 (Arabic Windows), CP1257 (Baltic Windows), 96Greek, GOST, TASS, MAZOWIA, KOI8-U **ISO character sets:** 8859/1 (Latin1), 8859/2 (Latin2), 8859/3 (Latin3), 8859/4 (Latin4), 8859/5 (Latin/Cyrillic), 8859/6 (Latin/Arabic), 8859/7 (Latin/Greek), 8859/8 (Latin/Hebrew), 8859/9 (Latin5), 8859/15 (Latin9)
Resident font	Draft, Courier, Gothic, DP Text, OCR-A, OCR-B
Resident Emulations	Epson ® FX Series - ESC/P, IBM ® Proprinter III XL, IBM ® Personal Printer 2381, ANSI, Compuprint native commands
Interfaces	Parallel - Serial - USB 2.0 - LAN Ethernet 10/100 or Parallel - Serial - USB 2.0 - LAN Ethernet 10/100/IPDS Input buffer 128 Kbytes - Plug&play (Windows environment)
Drivers and Sw	Windows 9X/2000/XP/Vista/W7/W8/W10/W11 - WinServer2008 - NOVEL - DOS NetViewMaster (complete printer management from remote) and Internal WEB Page (both available with LAN interface)
Reliability	**MTBF:** 20.000 hours
Print Head Life	800 Millions Characters
Ribbon life·	Black Long life ribbon 25 Millions Chracters
Noise Level	54 dBA
Power Supply	**Tension:** 100V - 240V **Frequency:** 60 Hz - 50 Hz
Power consumption·	120 W Max. (printing), 30 W (standby)
Physical Dimensions & Weight	670 (W) x 320 (H) x 450 (D) mm - 21 Kg

GDS Compuprint

Compuprint SALES CONTACTS

Italy: (+39) 011 9892 141 -
Other Countries: (+39) 011 9892 141 -
Website: www.compuprint.com
Email: sales@compuprint.com

Ordering Information

Printers and Supplies

Compuprint 9300e - Par/Ser/USB/Lan	PRTNE9300
Compuprint 9300e - Par/Ser/USB/Lan-IPDS	PRTNE9300I
Black ribbon 25MC	PRKN102-1

Options

Additional tractor	PRFN2TR6
Open pedestal	PRFN-PD1

Note 1 - The Compuprint 9300e measured performance herein declared are superior than any other competitive serial matrix printer model

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.
Copyright © 2025 GDS S.p.a. - Compuprint Division