

Manual or Automatic Banding for 20/30/40/50 mm band width

BM2530/2530W

- Compact Design
- 25 bundles/min.
- Band guides adjustable between 120 to 200 mm
- Thermoband PE-coated or PP-film band
- Manual or Automatic banding operation





Applications



RETAILS (FLYERS & BOOKS)



BANKS & POSTOFFICES (BANKNOTES)

BM2530/2530W Automatic Banding Machine

Features

Compact Design
Solid and Precise mechanical construction
Manual or Automatic banding operation
Closing the band by temperature sealing
Adjustable temperature sealing
Adjustable band guides
Adjustable try square to suite the product size
Adjustable band loop
Continuously adjustable banding tension



BM3E3UW

TECHNICAL DATA

		BM2530	BM2530W	
Product dimensions	Width	25 to 200 mm	25 to 250 mm	
	Height	5 to 150 mm	5 to 200 mm	
Band Guides adjustable between		120 to 200 mm		
Working Speed		25 bundles/min.		
Types of Band		Paper "kraft" (thermoband) – PE coated PP_band / film (polypropylene)		
Band Width		30mm	30 mm (20-40-50 mm on request)	
Band Roll outer diameter		145 mm max		
Band Roll Inner diameter		50 mm		
Weight		24 Kg	32,5 Kg	
Sound Level		Corresponding	Corresponding to DIN 45635/27	
Power Supply		220/230 Vac, 50 Hz – 180VA – 1 Ph 110 Vac, 60 Hz – 180VA – 1 Ph Different power supply on request		
Dimensions		410 x 320 x 350 mm (L-W-H)	490 x 320 x 350 mm (L-W-H)	
Regulatory		CE and RoHS		

DMOEON

PRODUCT MODELS

Automatic/Manual Banding Machine - Band Width- 30 mm. BM2530 Wide Automatic/Manual Banding Machine - Band Width 30 mm. BM2530W



Compuprint Sales Contact Italy: +39 011 9892141–133

email: sales@compuprint.com
website: www.compuprint.com



